

Fully Synthetic

# K1 Lube GX A3/B4

*Superior grade gasoline engine oil for Maximum performance*

ACEA A3/B4, API SL (5W-30),  
API SN (0W-40, 5W-40, 10W-40),  
VW 502.00/505.00



## DESCRIPTION

K1 Lube GX A3/B4 is a premium engine oil formulated with VHVI Group III base oils and high-quality and high-tech additives formulation. It is good for passenger cars without DPF or GPF with ACEA A3/B4. This engine oil provides long drain interval as well as good performance.

## APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars.
- Light truck gasoline engines.
- Gas-fuelled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
- Four-stroke gasoline engines in motorcycles and portable power equipment where the manufacturer recommends conventional passenger car motor oils.

## PERFORMANCE STANDARDS

ACEA A3/B4, API SL (5W-30), API SN (0W-40, 5W-40, 10W-40),  
VW 502.00/505.00

## CUSTOMER BENEFITS

### Extended Oil Drainage Interval

Outstanding oxidation property prevents the engine oil from losing its viscosity and allows engine oil to be used for a long time.

### Maximum engine life

Excellent detergent additives provide noticeable piston cleanliness and better sludge control, providing necessary engine protection and extend engine service life.

### High Quality VHVI Base Stock

Superior low temperature properties of Group III base oil make the start-up of engines easy at low temperature. Excellent thermal stability and oxidation stability of VHVI base oil protect suppress oil degradation and sludge formation inside engine.

## KEY PROPERTIES

SAE Viscosity	0W-40	5W-30	5W-40	10W-40
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	76.3	71.2	91.7	86.4
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	13.3	12.0	15.1	13.1
Viscosity Index	178	166	174	151
Pour Point, °C	-43	-38	-39	-32
Flash Point, COC, °C	226	240	232	250
Package (Liters)	1, 4T, 200	1, 4T, 200	1, 4T, 200	1, 4, 4T, 200