/FullySynthetic

K1 Lube DX C3

Premium diesel engine oil for Ultimate performance

ACEA C3-16, API SN/CF, MB 229.51/229.52, BMW Long Life-04, VW 502.00/505.00/505.01



DESCRIPTION

K1 Lube DX C3 is formulated with the latest VHVI synthetic base oil combined with additive technology that produces minimum sulfated ash, phosphorous and sulfur contents to meet the requirement of low SAPS oil.

K1 Lube DX C3 is suitable for passenger car mounted with gasoline or diesel engines, as well as SUV and RV.

K1 Lube DX C3 maintains engine durability while helps in extending the life of DPF and helps in increasing DPF performance by using additive of minimum sulfated ash contents.

K1 Lube DX C3 also helps extending the life of emission aftertreatment device such as SCR by introducing low phosphorous and sulfur content additive technology.

APPLICATIONS

- SUV and RV equipped with DPF, SCR and other emission aftertreatment system where an ACEA C3 performance engine oil is required.
- Light duty diesel engines and gasoline direct injection engines.
- Passenger cars where the manufacturers recommend API SN spec oils.
- Vehicles that requires MB, BMW specification performance.

PERFORMANCE STANDARDS

ACEA C3-16, API SN/CF, MB 229.51/229.52, BMW Long Life-04, VW 502.00/505.00/505.01

KEY PROPERTIES

SAE Grade	5W-30	15W-40
Kinematic Viscosity, mm ² /s @ 40°C	68.0	79.2
Kinematic Viscosity, mm ² /s @ 100°C	11.9	13.6
Viscosity Index	172	176
Pour Point °C	-36	-39
Flash Point °C	236	246
Package (Liters)	1,4T, 5, 200	1,4T, 5, 200