

# K1 Lube Brake

*Premium Performance  
Automotive Brake Fluid*

DOT 3, DOT 4



## DESCRIPTION

K1 Lube Brake is a premium, non-petroleum automotive brake fluid, designed for use in a wide range of conventional hydraulic brake and clutch systems in severe service conditions or where DOT fluids are recommended.

## PERFORMANCE STANDARDS

K1 Lube Brake meets and exceeds the requirements of the following specifications for DOT brake fluid. ISO 4925, FMVSS 116, SAE J1704

## CUSTOMER BENEFITS

### Excellent braking response

Low volatility minimizes vapor formation over a wide temperature range, ensuring good braking performance and providing an additional margin of safety against vapor lock under more severe service conditions.

### Reliable operation in severe service

High thermal and oxidation stability provides resistance to fluid degeneration and formation of harmful deposits, even under severe service conditions.

### Saves on maintenance

Compatible with all metallic, plastic and elastomer components, providing continuous corrosion protection and lubrication throughout the brake/clutch system.

### Reduces inventory costs

Widespread suitability for different motor vehicles as it may be used in systems designed for DOT 3, DOT 4.

## KEY PROPERTIES

FMVSS Grade	DOT 3	DOT 4
Boiling Point-Dry	240°C/464°F	262°C/500°F
Boiling Point-Wet	146°C/295°F	173°C/320°F
Kinematic Viscosity, cSt @ 40°C	1,300	1,100
Kinematic Viscosity, cSt @ 100°C	2.0	2.0
pH	8.8	8.0
Color	Amber	Amber
Package (Liters)	0.5, 200	0.5, 200